


OJR410

OJR412

OJR414

OJR416

OJR418

OJR520

INTERFACE SIZE	XS	S	M	L	XL	XXL
Weight (per kit)	6.7 g	7.1 g	9.3 g	13.5 g	13.8 g	28.2 g
Description	The F&P Optiflow™ Junior 2 Nasal High Flow Interface is an interface intended for use with a nasal high flow (NHF) therapy system to deliver heated and humidified NHF therapy to spontaneously breathing patients.					

PRODUCT SPECIFICATIONS

Connection	Easy-click connector					
Quantity	Box of 20					Box of 10
Box components	F&P Optiflow Junior 2 nasal interface, user instructions					
Packaging materials	Outer: cardboard box; interface clamshell: PET; user instruction: paper					
Packaging dimensions (L x W x H mm)	Box: 201 x 137 x 220					Box: 265 x 205 x 185

PERFORMANCE

Ambient range	18 – 26 °C / 64 – 79 °F
Usage	Single patient use
Duration of use	7 days
Storage temperature	Min: -10 °C / 14 °F, Max: +50 °C / 122 °F
Shelf life	3 years

COMPONENTS AND COMPOSITIONS

Predominant materials	Interface: Thermoplastic elastomer, hydrocolloid, ABS, stainless steel
Materials not present	Not manufactured with natural latex, PVC or phthalates (DEHP, DBP, BBP)
Manufacturing mode	Non-invasive device; produced in a controlled working environment
Disposal	Incineration or according to hospital protocol for interface; Clamshell packaging and label recyclable PET



INTERFACE SIZE		XS	S	M	L	XL	XXL
COMPATIBLE HUMIDIFIERS	CIRCUIT	FLOW RATES* (L/MIN)					
 MR850	RT330	0.5 – 8	0.5 – 9	0.5 – 10	0.5 – 23	0.5 – 25	1 – 36
	RT331	0.5 – 8	0.5 – 9	0.5 – 10	0.5 – 23	0.5 – 25	-
 AIRVO™ 2	900PT561, 900PT562	-	-	-	2 – 20	2 – 25	10 – 50
 F&P 950™ **	950N40/J	0.5 – 10	0.5 – 10	0.5 – 11	0.5 – 28	0.5 – 31	0.5 – 36
	950P40/J	1 – 10	1 – 10	1 – 11	1 – 34	1 – 36	1 – 60

COMPATIBLE SPARES

F&P Wigglepads 2	WJR110	WJR112	WJR114
Packaging dimensions (L x W x H mm) - Pack	110 x 85 x 30	113 x 82 x 25	
Packaging dimensions (L x W x H mm) - Case	172 x 124 x 30	175 x 125 x 32	
Quantity	Case: 40 each (2 packs of 20)		

REGULATORY

Classification	AU-IIa, EU-IIa, Canada-IIa, US-I	
Country of origin	New Zealand, Mexico	
Notified body	TÜV SÜD Product Services GmbH CE0123	
Standard	Medical tapers used comply with ISO 5356-1	
GTIN Code - OJ2 / OJ2+ Nasal Interface	OJR410	09420012435750
	OJR412	09420012435927
	OJR414	09420012435941
	OJR416	09420012435965
	OJR418	09420012435989
	OJR520	09420012453334
GTIN Code - Wigglepads 2	WJR110	09420012454829
	WJR112	09420012454812
	WJR114	09420012450135
GMDN Code	35201	

* Flow rates above describe technical capability of the product when used at sea level. Ensure clinical judgement is used when prescribing flow rates.

** F&P 950™ System may not be available in all countries

F&P 950™ System is currently not cleared for sale in the USA